

Safety Data Sheet according to Regulation (EC) Nr. 1907/2006

Revisions date: 29.04.2015

1. <u>Identification of the substance and of the company</u>	
Trade name:	DEGUSSIT® RUBY STONE
Product #:	3501002, 3501003, 3501012, 3501013, 3501052, 3501102, 3501103, 3501112, 3501113, 3501114, 3502002, 3502003, 3502011, 3502012, 3502013, 3502021, 3502022, 3502023, 3502032, 3502033, 3502102, 3502103, 3502111, 3502112, 3502113, 3502121, 3502122, 3502123, 3502131, 3502132, 3502133, 3502142, 3502143, 3502202, 3502203, 3502211, 3502212, 3502213, 3502311, 3502312, 3502401, 3502551, 3502553, 3502613, 3502702, 3502703, 3502711, 3502712, 3502713, 3502721, 3502722, 3502723, 3502731, 3502732, 3502733, 3502912, 3502913, 3503000
Supplier:	Paul H. Gesswein & Co., Inc. 201 Hancock Ave., Bridgeport, CT 06605 Phone: 203-366-5400, FAX: 203-366-3953 email: info@gesswein.com, www.gesswein.com
Emergency phone number: CHEMTELL - 800-255-3924	
2. Hazards identification Not classified as hazardous acc. to GHS or EC-regulation	
3. <u>Information on ingredients:</u>	
Characterisation:	chromium doped alumina
Main component:	Al ₂ O ₃
CAS – No:	1344-28-1
EINECS – No:	215-691-6
Hazardous ingredients:	none
4. First aid measures: No special measures necessary	
5. Firefighting measures: The product itself does not burn	
6. Accidental release requirements: No special measures necessary	
7. Handling and storage: Brittle material, handling accordingly	
8. Exposure controls and personal protection: No special measures necessary	
9. <u>Physical and chemical properties:</u>	
Appearance:	Physical state: solid ceramic product Colour: red Odour: none Density: approx. 3,9 g/cm ³
Safety relevant basic data:	Melting point: approx. 2050°C Flash point: not applicable Explosive limits: not applicable Ignition point: not applicable Water solubility: insoluble

Safety Data Sheet according to Regulation (EC) Nr. 1907/2006


Revisions date: 29.04.2015

10. Stability and reactivity: No disclosures required
11. Toxicological information: Not classified as toxic or hazardous
12. Ecological information: Without risk to the environment
13. Disposal considerations: According the local official regulations for ceramic materials
14. Transport information: Not dangerous cargo
15. Regulatory information: .A safety data sheet is not mandatory acc. 1907/2006/EU. Provide is voluntary.
16. Other information: The data given here is based on current knowledge and experience. The purpose of this Safety Data Sheet is to describe the product in terms of their safety requirements. The data does not signify any warranty with regard to the product's properties.

This safety data sheet was created with computer and is valid without signature.

SAFETY DATA SHEET

Gesswein®MOLDMAKERand MOLDMAKER PLUS FinishingStones

Section 1: Identification Of the Substance/Mixture And Of The Supplier	
<p>Supplier Paul H. Gesswein & Co., Inc. 201 Hancock Ave. Bridgeport, CT 06605</p> <p>Company Contact: John Harsh Telephone Number: 203-366-5400 E-Mail: jharsh@gesswein.com Web Site: www.gesswein.com</p>	<p>Manufacturer Paul H. Gesswein & Co., Inc. 201 Hancock Ave. Bridgeport, CT 06605</p> <p>Company Contact: John Harsh Telephone Number: 203-366-5400 E-Mail: jharsh@gesswein.com Web Site: www.gesswein.com</p>
<p>Supplier Emergency Contacts & Phone Number Chemtel: 800-255-3924</p>	<p>Manufacturer Emergency Contacts & Phone Number Chemtel: 800-255-3924</p>
<p>Issue Date: 05/14/2015</p> <p>Product Name: Gesswein® MOLDMAKER and MOLDMAKER PLUS Finishing Stones CAS Number: Not Established Chemical Family: carbide abrasive</p> <p>Synonyms abrasive stone bonded silicon carbide mold stone polishing stone</p> <p>Product/Material Uses Mold and die polishing, grinding, tool sharpening, dressing of grinding and cutting wheels. Vitrified silicon carbide abrasives break down during use. The resulting dust is classified by OSHA as inert or nuisance dust. Data provided pertains primarily to the dust produced during and after use. IMPORTANT: Hazards may change when this product is used in conjunction with solvents, cutting fluids or other chemicals. For more complete information, consult the Safety Data Sheet of chemical products used with vitrified silicon carbide abrasives.</p>	
Section 2: Hazards Identification	
	
<p>Hazard Classification(s) HAZARD CLASSIFICATION(S): Specific Target Organ Toxicity, Repeated Exposure: Category 3 (lung)</p> <p>SIGNAL WORD: WARNING</p> <p>HAZARD STATEMENTS: May cause respiratory irritation (H335)</p> <p>PRECAUTIONARY STATEMENTS: P261 - Avoid breathing mist, vapor or spray. P271 - Use only outdoors or in a well-ventilated area. P304+P340 - IF INHALED: remove person to fresh air and keep comfortable for breathing. P312 - Call a Poison Center or Doctor if you feel unwell. P403+P233 - Store in a well-ventilated place. Keep container tightly closed. P405 - Store locked up. P501 - Dispose of contents/container in accordance with local, state, federal and international regulation.</p>	

SAFETY DATA SHEET

Gesswein® MOLDMAKER and MOLDMAKER PLUS Finishing Stones

Section 3: Composition/Information On Ingredients

Ingredient Name	CAS Number		Percent Of Total Weight
cured marking ink	NA	<	1
frit/clay	65997-18-4		5 - 30
silicon carbide, non-fibrous	409-21-2		60 - 95

Vitrified silicon carbide abrasives are ceramic articles that may be further treated with cured resin, oil or wax. End use of vitrified silicon carbide abrasives (i.e., grinding, polishing) may produce dust which is classified as inert or nuisance dust.

Product may contain trace concentrations of crystalline silica.

Section 4: First Aid Measures

Eye

Hold eyelids apart and flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately if irritation or blurred vision develops and persists.

Skin

In case of contact, wash skin with soap and water. Get medical attention if irritation (redness, rash, blistering) develops and persists.

Ingestion

Call a physician or a poison control center immediately in case a large amount is accidentally swallowed. No treatment is thought to be necessary for ingestion of small amounts of dust. Rinse mouth with water.

Inhalation

Remove person from source of exposure to fresh air. Get medical attention if irritation, coughing, sneezing or shortness of breath develops and persists.

Section 5: Fire Fighting Measures

Flammability Class: None flammable or combustible.

Fire And Explosion Hazards

Not applicable for untreated silicon carbide abrasives. Oils, wax or solvents applied to the stone or tools may be flammable - see (M)SDS for chemicals used during tool sharpening.

Extinguishing Media

Use the appropriate extinguishing media for the surrounding fire - water spray, carbon dioxide, dry chemical, foam.

Fire Fighting Instructions

Not applicable for untreated silicon carbide abrasives. Consulting fire fighting instructions for oils, waxes and solvents applied to stone.

Section 6: Accidental Release Measures

Small amounts of dust may be swepted up into a suitable, closeable container for disposal. Use a vacuum or wet clean-up methods, such as water mist, for large amounts of dust. Avoid generating airborne dust.

Section 7: Handling And Storage

Handling Precautions

Avoid generating airborne dust. Use with adequate ventilation to control dust. Do not use compressed air, or shake clothing, rags or other items, to remove dust. Remove dust by washing or vacuuming. See ANSI Standard B7.1 safety requirements for the use of abrasive grinding wheels.

SAFETY DATA SHEET

Gesswein® MOLDMAKER and MOLDMAKER PLUS Finishing Stones

Section 7: Handling And Storage - Continued

Storage Precautions

Not applicable.

Work/Hygienic Practices

Use good personal hygiene. Wash thoroughly with soap and water after handling.

Section 8: Exposure Controls/Personal Protection

Engineering Controls

Use with adequate general and local exhaust ventilation. Local exhaust ventilation should be provided, if possible, to maintain exposures below recommended occupational exposure limits. Used good housekeeping and hygiene practices.

Eye/Face Protection

Goggles or faceshield over safety glasses should be worn when using the product for grinding, cutting and polishing.

Skin Protection

Protective gloves, such as leather work gloves, are recommended but not required when using abrasives. However, use gloves with care around rotating grinding wheels or similar equipment where gloves and clothing may get caught in pinch points on the grinders.

Respiratory Protection

General room ventilation is normally adequate. Engineering controls should be implemented preferentially to reduce exposures. In case of inadequate ventilation, use NIOSH-approved 95-series respirator for dust. Note that R or P-series dust filters may be necessary when using cutting oils on abrasives. The level of respiratory protection needed should be based on the required protection factor after evaluating chemical exposures using appropriate industrial hygiene monitoring and/or OSHA guidance.

Other/General Protection

Hearing protection, such as muffs or plugs, should be used for high noise levels during grinding. Get medical attention in the event of hearing problems or ringing in the ears.

Ingredient(s) - Exposure Limits

silicon carbide, non-fibrous

ACGIH TLV-TWA: 10 mg/m³ (inhalable dust)

ACGIH TLV-TWA: 3 mg/m³ (respirable dust)

OSHA PEL-TWA: 15 mg/m³ (total dust)

OSHA PEL-TWA: 5 mg/m³ (respirable dust)

NIOSH REL-TWA: 10 mg/m³ (total dust, 10 hrs)

NIOSH REL-TWA: 5 mg/m³ (respirable dust, 10 hrs)

Section 9: Physical And Chemical Properties

Appearance

Solid, green, gray or black block or wheel.

Odor

Odorless for untreated silicon carbide abrasives. Slight paraffin odor for oil or wax treated products.

Chemical Type: Mixture

Physical State: Solid

Specific Gravity: 1.5 to 2.5

Percent Volatiles: NA

Percent VOCs: NA

Vapor Pressure: NA

Vapor Density: NA

SAFETY DATA SHEET

Gesswein® MOLDMAKER and MOLDMAKER PLUS Finishing Stones

Section 9: Physical And Chemical Properties - Continued

Solubility: insoluble
Evaporation Rate: NA

Section 10: Stability And Reactivity

Stability: Stable
Hazardous Polymerization: Will not occur

Conditions To Avoid (Stability)

Not applicable for untreated silicon carbide abrasives. See (M)SDSs for waxes, oils or solvents applied to abrasives. May be flammable. May evolve toxic or irritating thermal decomposition products.

Incompatible Materials

Not applicable for untreated silicon carbide abrasives. See (M)SDSs for waxes, oils or solvents applied to abrasives.

Hazardous Decomposition Products

Not applicable for untreated silicon carbide abrasives. See (M)SDSs for waxes, oils or solvents applied to abrasives. May be flammable. May evolve toxic or irritating thermal decomposition products.

Section 11: Toxicological Information

Eye Effects

Dust can scratch the cornea and cause mechanical irritation, resulting in redness and watering of the eyes and blurred vision.

Skin Effects

Contact with dust may cause mechanical irritation, resulting in redness and rash of the skin. Although product is not expected to be a significant skin irritant.

Acute Oral Effects

Ingestion is not an anticipated route of exposure due to the physical form of the product. However, small amounts may be ingested from contact of contaminated hands with the mouth, such as during eating and smoking. Abrasive particles may cause mechanical irritation of the mouth and throat.

Acute Inhalation Effects

Inhalation is not anticipated directly from the product. However, dust generated from grinding and polishing may be inhaled. High dust concentrations may cause nose and throat irritation, sneezing and coughing.

Long-term inhalation of dust may decrease the ability of the lungs to clear particulate matter, which may cause shortness of breath and increased susceptibility to respiratory disease, pneumoconiosis. There is an increased risk of developing tuberculosis if pneumoconiosis develops.

Subchronic (Target Organ Effects)

Grinding may create high noise and vibration levels which could affect or damage hearing. High noise levels may result in hearing loss and/or tinnitus (ringing in the ears). Prolonged or repeated exposure to excessive vibration may cause circulatory effects in the hands. Prolonged or repeated exposure to vibration may result in a tingling or numbness sensation of the fingers and hands (i.e., Reynauds Disease).

Chronic/Carcinogenicity

Product does NOT contain fibrous silicon carbide. Non-fibrous silicon carbide is not considered to be carcinogenic by NTP, IARC, OSHA or ACGIH.

Product may contain trace amounts of crystalline silica. Prolonged exposure to crystalline silica may cause silicosis of the lungs, a severely disabling, progressive and often fatal pulmonary disease. Crystalline silica is characterized as a known human carcinogen by the National Toxicology Program (NTP) and is listed as an IARC Group 1 human carcinogen.

SAFETY DATA SHEET

Gesswein® MOLDMAKER and MOLDMAKER PLUS Finishing Stones

Section 11: Toxicological Information - Continued

Conditions Aggravated By Exposure

Nuisance dust may aggravate pre-existing lung conditions.

Ingredient(s) - Toxicological Data

frit/clay

LD50 (oral, rat): >3,000 mg/kg

Section 12: Ecological Information

Ecotoxicological Information

No ecotoxicological information is available. However, untreated silicon carbide abrasives are not expected to represent a significant ecological hazard.

Section 13: Disposal Considerations

Dispose in accordance with applicable federal, state and local government regulations. Dispose of bulk amounts in an environmentally responsible manner. Untreated silicon carbide abrasives can generally be disposed in an approved sanitary landfill.

Section 14: Transport Information

Proper Shipping Name

Not regulated for transportation.

Section 15: Regulatory Information

U.S. Regulatory Information

All ingredients of this product are listed or are excluded from listing under the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

SARA Hazard Classes

Chronic Health Hazard

SARA Section 313 Notification

This product does not contain any ingredients regulated under Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 or 40 CFR 372.

Ingredient(s) - State Regulations

silicon carbide, non-fibrous

New Jersey - Workplace Hazard

Pennsylvania - Workplace Hazard

Section 16: Other Information

NFPA Rating

Health: 0

Fire: 0

Reactivity: 0

HMIS Rating

Health: 0

Fire: 0

Reactivity: 0

SAFETY DATA SHEET

Gesswein® MOLDMAKER and MOLDMAKER PLUS Finishing Stones

Disclaimer

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained therein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purpose(s).

Paul H. Gesswein & Co., Inc.

Printed Using MSDS Generator™ 2000